



AIF S.L.

AUTOMATION IN FOUNDRIES



**MOLD RELEASE LIQUID
RESERVOIR**

SprayTank

MOLD RELEASE LIQUID RESERVOIR

SprayTank provides a constant supply of release agent to the lubricator at the pressure and flow required by the customer by means of the product propelling pump.

SprayTank can pump up to 50 liters/minute.



With SprayTank you have total control of the release agent that is provided to the lubricator.

Also allows to regulate the pressure of the product going out between 1 and 6 bars keeping it constant for an optimal subminister to the machine.

SprayTank has level sensors and light signals to warn of the low level of release product in the tank.

AVAILABLE VERSIONS:

SPRAYTANK MIX Mezclador de desmoldeante

- Automatic mixing with electronic pump or mechanical system.
- Tank finished in stainless steel.
- Control by plc.
- High durability pump.
- Wheels for easy mobility.
- Connector for interface with the machine.

SPRAYTANK

- Tank finished in stainless steel.
- Control by plc.
- High durability pump.
- Wheels for easy mobility.
- Connector for interface with the machine.

SprayTank MIX allows you to realise the mixing of the release agent and water automatically, with the possibility of regulating the concentration of the mixture according to the customer's needs and providing an optimal subminister to the lubricator.



AIF S.L.

AUTOMATION IN FOUNDRIES

Rambla Països Catalans, 18 Nave 45
08800 - Vilanova i la Geltrú - Barcelona
info@aifsl.es